

Proxima Ultralight DS2 Projector

Technical and Functional Specifications

Native Resolution	<ul style="list-style-type: none">● SVGA (800 x 600)
Resolution Supported	<ul style="list-style-type: none">● VGA (640 x 480), SVGA (800 x 600), XGA (1024 x 768)
Brightness	<ul style="list-style-type: none">● 800 ANSI lumens
Brightness Uniformity	<ul style="list-style-type: none">● 75%
Contrast Ratio	<ul style="list-style-type: none">● 250 to 1
Computer Compatibility	<ul style="list-style-type: none">● IBM PC or compatible● Apple Macintosh
Video Compatibility	<ul style="list-style-type: none">● NTSC, NTSC 4.43, PAL, PAL-N, PAL-M, SECAM
Display Technology	<ul style="list-style-type: none">● single-chip DLP
Number of Colors	<ul style="list-style-type: none">● 16.7 million colors
Input Sources	<ul style="list-style-type: none">● 1 composite video, 1 S-video, 1 computer
I/O Interface	<ul style="list-style-type: none">● PS/2
H-Sync Range	<ul style="list-style-type: none">● 31-85 kHz
V-Synch Range	<ul style="list-style-type: none">● 55-90 Hz
Bandwidth	<ul style="list-style-type: none">● up to 140 MHz
Keystone Correction (Digital)	<ul style="list-style-type: none">● $\pm 7^\circ$
Projection Lens	<ul style="list-style-type: none">● focal length: 31 to 40 mm, F 2.8 to 3.1
Projection Distance	<ul style="list-style-type: none">● 4.9 ft. to 16.4 ft. (1.5 m to 5 m)
Zoom	<ul style="list-style-type: none">● 1.3:1 manual zoom
Aspect Ratio	<ul style="list-style-type: none">● 4:3
Image Size (diagonal)	<ul style="list-style-type: none">● 1.2 ft. to 11.5 ft. (0.4 m to 3.5 m)
Throw Ratio	<ul style="list-style-type: none">● 2M/45"
Projection Method	<ul style="list-style-type: none">● front/rear, desktop/ceiling
Audio	<ul style="list-style-type: none">● 2 watt mono
Remote Control	<ul style="list-style-type: none">● Full function remote with mouse control and laser pointer
Lamp (Life)	<ul style="list-style-type: none">● 150 watt (1500 hours)
Dimensions	<ul style="list-style-type: none">● 8.25 in. W x 10.0 in. L x 3.2 in. H 20.9 cm W x 25.4 cm L x 8.0 cm H (base unit only)
Weight	<ul style="list-style-type: none">● 5.2 lbs. (2.4 kg)
Power Consumption	<ul style="list-style-type: none">● 250 watts
Power Requirements	<ul style="list-style-type: none">● 100 to 240V at 50/60 Hz
Operating Temperature	<ul style="list-style-type: none">● 50° to 104° F (10° to 40° C)
On-Screen Languages	<ul style="list-style-type: none">● English, French, Spanish, Portuguese, German, Italian, Chinese
Audible Noise	<ul style="list-style-type: none">● < 40 db
Approvals	<ul style="list-style-type: none">● FCC Class A, UL, c-UL, CE, TUV
Warranty	<ul style="list-style-type: none">● two years on parts and labor● 90 days limited on lamp● two years of ProXchange replacement service